



# **BAVARIA®** Mobile Dry Chemical Powder Fire Extinguishers Stored Pressure Operated

Type

## CONCORD-50M



Gold Series

### Applications:

BAVARIA CONCORD-50M is a rapid intervention, one man operational unit for effective fire fighting



**BAVARIA** EGYPT (S.A.E.)  
Gisir El Suez St. Block 109, Industrial Zone,  
Ismailia Desert Road, Cairo-Egypt  
P O Box: 2016/11111 Cairo-Egypt

Tel. : + 20 (2) 2698 9443 / 5 / 6  
Fax : + 20 (2) 2698 8447  
Website : [www.bavaria-firefighting.com](http://www.bavaria-firefighting.com)  
Email : [international.sales@bavaria.com.eg](mailto:international.sales@bavaria.com.eg)



**BAVARIA** Brandschutz Industrie GmbH & Co. KG  
Regensburger Strabe 16,  
D-93449 Waldmunchen  
Germany

Tel. : + 49 (0) 9972 9401-0  
Fax : + 49 (0) 9972 9401-17  
Website : [www.bavaria-firefighting.de](http://www.bavaria-firefighting.de)  
Email : [info@bavaria-firefighting.de](mailto:info@bavaria-firefighting.de)



## BAVARIA® Mobile Dry Chemical Powder Fire Extinguishers - Stored Pressure Operated

Type: **CONCORD-50M** - Gold Series ★★★★★

### Features:

- A one man-operational unit
- High extinguishing efficiency
- Allows repeated operation and intermittence at will
- Equipped with a pressure filling/release valve and a pressure gauge
- Equipped with a 5 m high pressure reinforced rubber hose for easy manoeuvring
- Equipped with a heat and an electricity-isolated operating pistol
- Supported on a carriage with two rear rollers and a front directional roller for easier manoeuvring with chemical-resistant tyres
- Affords highest extinguishing rating due to its special multipurpose BAVARIA dry chemical powder "BAVARIA Extra Powder" (ABC)
- Suitable for electrical equipment up to 1000 V, at minimum distance 1 m



Manufactured According to European Standard DIN/EN 1866

Certified According to Egyptian Standard ES 1494

TÜV Approved Pressure Vessel

Awarded CE Mark

The Company Certified according to Quality, Environment and BS-OHSAS Management Systems ISO 9001, ISO 14001  
Bavaria Laboratory Accredited According to the ISO/IEC 17025

### Technical Specifications:

Capacity	50 kg
Extinguishing Rating	A IIBC
Working Temperature Range	-20° C to 60° C
Testing Pressure	35 bar
Bursting Pressure	Over 70 bar
Valve Material	Chrome plated brass alloy with a manometer & filling/release valve
Discharge Pistol Material	Special engineered polymer
Shell Material	Steel according to DIN EN 10025
Extinguishing Agent	MAP-based "BAVARIA Extra Powder"
High Pressure Rubber Hose Length	5 m
Paint Finish	Surface treatment and 100% polyester coating
Approx Gross Weight	116 kg

### Warranty:

Period of Warranty	2 Years
Coverage of the Warranty	Against material failure and production defects
Method of Warranty Coverage	Limited to the replacement of the defected part or product after verification that the failure is covered by the scope of the warranty
Warranty Exclusions	Failures due to misuse, mishandling, or inspection or repair by an unauthorized dealer or entity

\* The illustrations may show optional extras only available at extra charge. BAVARIA retains the right to alter specifications and illustrations given herein without prior notice. Specifications will only be considered communicated at placing of order.